



Inlet/Outlet

Size: 127mmx127mmx38mm
 Airflow: 199~257m³/hr
 117~151CFM
 Weight: 520g
 Noise: 42~49dBA
 Impeller: PA6 UL94V-0 Reinforced Plastic
 Frame: Aluminum Alloy
 Terminals: 0.5mm
 Lead Wire: AWG#24 UL 1430
 (Optional)
 Motor: Capacitor-Run Induction Motor
 Safety: UL.CUL.TUV.CE
 Operaton Temperature: -10°C~+65°C

Unit:mm

Model	Bearing System	Voltage VAC	Freq. Hz	Current A	Power W	Speed RPM	Noise dBA	Air Flow		Static Pressure (mmH ₂ O)	Weight Gram
								M ³ /hr	CFM		
RAH1278S1-C	Sleeve	220~240	50/60	0.12/0.12	25/25	2600/3050	43/47	206/243	121/143	8.8/11.4	520
RAM1278S1-C		220~240	50/60	0.09/0.09	20/20	2500/2750	42/45	199/221	117/130	7.1/6.6	
RAH1278S2-C		100~125	50/60	0.21/0.21	25/25	2600/3050	43/47	206/243	121/143	8.8/11.4	
RAM1278S2-C		100~125	50/60	0.16/0.16	20/20	2500/2750	42/45	199/221	117/130	7.1/6.6	
RAH1278B1-C	Ball	220~240	50/60	0.12/0.12	25/25	2800/3300	45/49	224/257	132/151	10.3/13.0	
RAM1278B1-C		220~240	50/60	0.09/0.09	20/20	2500/2900	42/46	199/233	117/137	7.1/8.6	
RAH1278B2-C		100~125	50/60	0.21/0.21	25/25	2800/3300	45/49	224/257	132/151	10.3/13.0	
RAM1278B2-C		100~125	50/60	0.16/0.16	20/20	2500/2900	42/46	199/221	117/137	7.1/8.6	

